TECHNICAL DATA SHEET Round bucket / DL-BR 110

LUDVIK SINCE 1993 CZECH REPUBLIC

basic data

full capacity	12000 ml
usable capacity	11000 ml
weight | bucket + plastic handle	320 g
weight tolerance	± 8 g
diameter	Ø 290 mm
height	v 222 mm
handle type	plastic | metal bail handle
color	white|black|yellow|individual *
seal lock	YES
IML	YES



logistics**

carton	16 pcs/carton
single pallet | 80 x 120	495 pcs/pallet
stackable***	YES

material

type	PP
intended use	FOOD | NON-FOOD

lid

DL-BL 290 - sealing lid



weight	80 g ± 5 g tolerance
IML	YES
logistics	16 pcs/ carton
	495/990/1980 pcs/pallet
material	PP
intended use	FOOD | NON-FOOD


DL-BF 290 - snap-on lid




weight	84 g ± 5 g tolerance
IML	YES
logistics	16 pcs/carton
	495/990/1980 pcs/pallet
material	PP
intended use	FOOD | NON-FOOD

handle

plastic



metal bail handle




accessories

- reinforcement for pump
- pump
- venting membrane
- custom color*

label

- IML label
- labeling service



*only when ordering four pallets or more

**The product must be transported in a clean, dry, and enclosed vehicle that does not pose any risk to its quality. If the outdoor temperature during transport is below 0 °C, the product should be kept in a room with a positive temperature for 24 hours before further use.

***Dynamic: Maximum load – 40 kg top load on the bottom container at 23 °C for 8 weeks. Stackability depends on many factors; therefore, the above data are for guidance only. Customers are advised to conduct internal tests to verify the suitability of stacking and transportation according to their specific conditions and requirements.